

UAB "Metalistas LT" Šermukčnių g. 19. Panevėžys LT-85113, Lietuva

Interés kodas 247736790

Bankas AB DNB bankas A/a: 1727 4010 0510 0184 1963 Tel +370 614 8916

info@metaledas fl vvvvv metalistas fl

DECLARATION OF PERFORMANCE No. 4

1. UNIQUE IDENTIFICATION CODE OF THE PRODUCT-TYPE:

Connectors for timber structures – nail plates:

Parameters (type) of the product - dimensions in mm, number of holes.					
The nominal size of holes - 5 mm.					
20x80x2,	4	60x300x2	45	160x400x2 160	
40x80x2,	8	80x200x2	40	200x220x2 110	
40x100x2	10	80x240x2	48	200x300x2 150	
40x120x2	12	80x300x2	60	160x180x2 40	
40x140x2	14	100x140x2	35	160x220x2 40	
40x160x2	16	100x160x2	40	40x1250x2 124	
40x200x2	20	100x200x2	50	60x1250x2 168	
40x400x2	40	100x240x2	60	35x100x2.5 8	
40x300x2	32	100x260x2	65	40x180x3 16	
40x600x2	60	100x300x2	75	55x140x3 16	
50x160x2	20	100x400x2	100	Plates with holes divided	
50x200x2	25	120x140x2	45	by length:	
50x240x2	30	120x240x2	72	20x2 (10-metre strap)	
60x120x2	18	120x300x2	90	20x2 (25-metre strap)	
60x140x2	21	140x200x2	70	40x2 (25-metre strap)	
60x160x2	24	140x240x2	84	40x2 (50-metre strap)	
60x200x2	30	140x260x2	91	60x2 (25-metre strap)	
60x240x2	36	160x200x2	80	60x2 (20-metre strap)	

A specific product is indicated with the CE marking on the packaging.

2. INTENDED USED:

For load-bearing timber structures of buildings and civil engineering works.

3. MANUFACTURER:

"METALISTAS LT" UAB

Šermukšniu St. 19, LT-35113 Panevėžys www.metalistas.lt, info@metalistas.lt

Tel.: +3706 1499167; Fax: 8 45 583008

4. AUTHORIZED REPRESENTATIVE:

--



UAB "Metalistas LT" Šermukšnių g. 19, Panevėžys LT-35113, Lietuva [monés kodas 247736790 PVM kodas LT477367917 Bankas AB DNB bankas A/s: LT27 4010 0510 0184 1067 Tel. +370 614 99167 Faks. +370 45 583008 info@metalistas.tt www.metalistas.tt

5. SYSTEM OF ASSESSMENT AND VERIFICATION OF CONSTANCY OF PERFORMANCE: 2+

6. HARMONIZED STANDARD

EN 14545:2008 (LST EN 14545:2009)

Notified body:

1397, State Enterprise Construction Products Certification Centre (SPSC)

7. DECLARED PERFORMANCE

Essential characteristics	Performance
Mechanical strength and rigidity: - steel strength at yield R_e - steel elongation at break A_{80}	≥ 280 MPa ≥ 22 %
Durability: the steel DX51D was hot-dip zinc coa on both sides of the plate - 275 g/m².	ted Z275, nominal weight of the zinc coating

on both sides of the plate - 275 g/m². The plates are intended for use in structures operating in accordance with the 2nd operating class under LST EN 1995-1-1.

Dimensions and tolerances comply with the requirements of the following standards: LST EN 14545 and LST EN 10143.

The indicated performance of the product is in conformity with the declared performance. This declaration of performance is issued in accordance with the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed (for and on behalf of the manufacturer) by:

Quality Manager

Darius Bumblys

Panevezys, 30 September 2016